

Data Sheet

Whalebone



Significant dimensions and patterns - when you require something extra of your room.

HØRNING Whalebone is available in two selections, solid or engineered with 4 or 6 mm wear layer.

Environmental certifications are provided on request.

Please contact us if you want special solutions, alternative wood species/dimensions or have questions about e.g. delivery time.

Whalebone– Data Sheet

HØRNING Whalebone is available in two variants, solid and engineered with 4 or 6 mm wear layer.

Dimensions and structure

Solid

Thickness: 16 / 20 mm
 Width: 100 / 120 / 150 mm
 Length: 600 / 800 / 1000 mm

Engineered

Thickness: 16 / 20 mm
 Width: 100 / 120 mm
 Length: 500 / 580 mm

Other dimensions and types of wood are available on request.

Wood species: Oak, smoked oak

Other wood species are available on request.

Tolerances

Width: +/- 0.2 mm
 Height: +/- 0.2 mm
 Perpendicular: Up to 0.2 mm

Moisture content: 8% (+/- 2%)

Profile: Tongue and groove on all four sides and with sharp edges or micro-bevel on all four sides.

Surface: Delivered untreated as standard. Can be delivered with a finished surface treatment with oil or varnish.

Grades:

Grades vary from wood specie and dimension. Wood is a natural material, thus there will always be variations compared to descriptions and photos. Samples will only show dimension and construction and not the grade. It is certain that variations will exist between small samples and the actual deliveries.

Exquisit

General uniform colour and wood structure. Variations due to growth conditions will exist. In principle free of knots and sapwood. Whirls, small scratches, cross grains and brown heart may be found to a small extent.

Living

A more characteristic look with natural colours and wood structure. In principle free of open knots, cracks, pith etc. Whirls, healthy knots, small scratches, cross grains and silicon stains may be found. Sapwood or brown heart will be found depending of the wood specie.

Country

A very characteristic look with all-natural colour variations and structures. Knots, sapwood and brown heart is found.

Very small open knots and scratches may be found.

Underfloor heating

Underfloor heating may be used. Please see the installation guide.

Indoor climate

It is important that the surface temperature never exceeds 27 degrees.

The relative humidity in the air (R.H.) must always be between 35-65% before, during and after installation.

Always study the installation guide from HØRNING prior to installation.

Fire class

Dfl-s1 Ask for our Declaration of Performance (DOP).

Environment

FSC and/or PEFC available upon request.

HØRNING is Eurofins Indoor Air Comfort Gold certified and offers a wide range of certified products.

With EPD, HØRNING can document the carbon footprint of selected products.

CE Marking

HØRNING floors are CE-certified in accordance with the EU declaration for indoor-use wood floors; EN 14342.